


Picnic with Professors

12pm March 3rd & 17th @ HFH

First year + transfer students are invited to join CS professors for a casual picnic at/outside Harold Frank Hall (HFH)! Bring your own drink, we'll bring the pizza! Follow link or scan QR code to fill out sign-up form!



<http://bit.ly/3Ztuixt>

Help improve Computer Science
at University of California-Santa
Barbara

Take the annual Computing
Research Association (CRA)
Survey!



<https://bit.ly/UCSB-DataBuddies-2023>



STACK C++ STL & TEMPLATES INTERVIEW PRACTICE

Problem Solving with Computers-II

C++

```
#include <iostream>
using namespace std;

int main(){
    cout<<"Hola Facebook!";
    return 0;
}
```


Announcements

- Pa02 released, **due 3/14** (Tuesday of Week 10)!
 - Choose data structures to answer questions about a movie data set
 - Analyze and optimize time and space complexity
 - Start early!
- Midterm grades released!
 - Max: 100% (13 students)
 - Median: 87%
 - Mean: 85%

Stack ADT

- Uses the Last In First Out (LIFO) principle
- Methods

- push() $O(1)$
- pop() $O(1)$
- top() $O(1)$
- empty() $O(1)$



C++STL

- The C++ Standard Template Library is a handy set of three built-in components:
 - Containers: Data structures
 - Iterators: Standard way to search containers
 - Algorithms: These are what we ultimately use to solve problems

C++ STL container classes

array
 vector
 forward_list
 list
 set
 stack
 queue
 priority_queue

multiset (non unique keys)

deque
 unordered_set
 map
 unordered_map
 multimap
 bitset

130 AB

single linked-list
 double linked list
 balanced BST
 $H = O(\log N)$

Finding the Maximum of Two Integers


- Here's a small function that you might write to find the maximum of two integers.

```
int maximum(int a, int b)
{
    if (a > b)
        return a;
    else
        return b;
}
```

One Hundred Million Functions...

Suppose your program uses 100,000,000 different data types, and you need a maximum function for each...

```
int maximum(int a, int b)
{
    if (a > b)
        return a;
    else
        return b;
}
```



A Template Function for Maximum

When you write a template function, you choose a data type for the function to depend upon...



```
template <class Item>
Item maximum(Item a, Item b)
{
    if (a > b)
        return a;
    else
        return b;
}
```

```
maximum (10, 20);
maximum ("Apple", "Banana");
```

Lab05 - BST with templates

BST, without templates:

```
class BSTNode {
public:
    BSTNode* left;
    BSTNode* right;
    BSTNode* parent;
    int const data;

    BSTNode( const int& d ) :
        data(d) {
        left = right
            = parent = nullptr;
    }
};
```

BST, with templates:

```
template<class Data>
class BSTNode {
public:
    BSTNode<Data>* left;
    BSTNode<Data>* right;
    BSTNode<Data>* parent;
    Data const data;

    BSTNode( const Data & d ) :
        data(d) {
        left = right
            = parent = nullptr;
    }
};
```

Handwritten: \hookrightarrow `BSTNode<int> n;`

BST, with templates:

```
template<class Data>
class BSTNode {
public:
    BSTNode<Data>* left;
    BSTNode<Data>* right;
    BSTNode<Data>* parent;
    Data const data;
```

```
    BSTNode( const Data & d ) :
        data(d) {
        left = right = parent = nullptr ;
    }
};
```

How would you create a **BSTNode** object on the runtime stack?

- declare*
- A. BSTNode n(10);
 - B. BSTNode<int> n; *no default constructor*
 - C. BSTNode<int> n(10);
 - D. BSTNode<int> n = new BSTNode<int>(10);
 - E. More than one of these will work

{ } syntax OK too

BST, with templates:

```
template<class Data>
class BSTNode {
public:
    BSTNode<Data>* left;
    BSTNode<Data>* right;
    BSTNode<Data>* parent;
    Data const data;

    BSTNode( const Data & d ) :
        data(d) {
        left = right = parent = nullptr ;
    }

};
```

How would you create a **pointer** to BSTNode with integer data?

- A. BSTNode* nodePtr;
- B. BSTNode<int> nodePtr;
- C. BSTNode<int>* nodePtr;

BST, with templates:

```
template<class Data>
class BSTNode {
public:
    BSTNode<Data>* left;
    BSTNode<Data>* right;
    BSTNode<Data>* parent;
    Data const data;

    BSTNode( const Data & d ) :
        data(d) {
        left = right = parent = nullptr ;
    }

};
```

Write a line of code to create a new BSTNode object with int data on the heap and assign nodePtr to point to it.

```
template<typename Data>
class BST {

private:
    BSTNode<Data>* root; //Pointer to the root of this BS

public:
    /** Default constructor. Initialize an empty BST. */
    BST() : root(nullptr){ }

    void insertAsLeftChild(BSTNode<Data>* parent, const Data& item){
        // Your code here

    }
}
```

Working with a BST: Insert

```
//Assume this is inside the definition of the class
void insertAsLeftChild(BSTNode<Data>* parent, const Data& item)
{
    // Your code here
}
```

Which line of code correctly inserts the data item into the BST as the left child of the parent parameter.

A. `parent.left = item;`

B. `parent->left = item;`

C. `parent->left = BSTNode(item);`

D. `parent->left = new BSTNode<Data>(item);`

E. `parent->left = new Data(item);`

Working with a BST: Insert

```
void insertAsLeftChild(BSTNode<Data>* parent, const Data& item) {  
    parent->left = new BSTNode<Data>(item);  
  
}
```

Is this function complete? (i.e. does it do everything it needs to correctly insert the node?)

- A. Yes. The function correctly inserts the data
- B. No. There is something missing.

What is difference between templates and typedefs?

```
template <class Item>
Item maximum(Item a, Item b)
{
    if (a > b)
        return a;
    else
        return b;
}
```

```
typedef int item;
item maximum(item a, item b)
{
    if (a > b)
        return a;
    else
        return b;
}
```

Template classes: Non-member functions

↳ template <const>
class BST;

BST operator+(const BST& b1, const BST&b2);

3:

↳ template <class T>
BST<T> operator+(const BST<T>& b1, const BST<T>&b2);

Template classes: Member function definition

For the compiler a name used in a template declaration or definition and that is dependent on a template-parameter is assumed not to name a type *unless* its preceded by a typename

```
template<class T>
class BST{
    //Other code
    Node* getNodeFor(T value, Node* n) const;
};
```

template <class T>
typename BST<T>::Node * BST<T>::getNodeFor(T value, Node * n) const;

Template classes: Including the implementation

```
//In bst.h  
class BST{  
//code  
};
```

```
#include "bst.cpp"
```

How to Convert a Container Class to a Template

1. The template prefix precedes each function prototype or implementation.
2. Outside the class definition, place the word `<Item>` with the class name, such as `bag<Item>`.
3. Use the name `Item` instead of `value_type`.
4. Outside of member functions and the class definition itself, add the keyword *typename* before any use of one of the class's type names. For example:

```
typename bag<Item>::size_type
```
5. The implementation file name now ends with `.template` (instead of `.cxx`), and it is included in the header by an include directive.
6. Eliminate any using directives in the implementation file. Therefore, we must then write `std::` in front of any Standard Library function such as `std::copy`.
7. Some compilers require any default argument to be in both the prototype and the function implementation.


Have you given a technical interview before?

A. Yes

B. No

Tips for Technical Interviews

1. Listen carefully
2. Draw an example
3. State the brute force or a partially correct solution
 - then work to get at a better solution
4. Optimize:
 - Make time-space tradeoffs to optimize runtime
 - Precompute information: Reorganize the data e.g. by sorting
5. Solidify your understanding of your algo before diving into writing code.
6. Start coding!



Small group exercise

Write a ADT called minStack of numbers that provides the following

- push() // inserts an element to the “top” of the minStack
- pop() // removes the last element that was pushed on the stack
- top () // returns the last element that was pushed on the stack
- min() // returns the minimum value of the elements stored so far

