

THE RULE OF THREE (CONT.) LINKED LISTS WITH CLASSES

Problem Solving with Computers-II

C++

```
#include <iostream>
using namespace std;

int main(){
    cout<<"Hola Facebook\n";
    return 0;
}
```



Last lecture:

- Modified the Complex class member variables to be pointers
- Wrote user-defined versions of the
 - Constructor
 - Destructor
 - Copy-constructor

Assume:


- * **User-defined destructor**
- * **User-defined copy constructor**
- * **Default copy assignment**

```
class Complex
{
private:
    double *real;
    double *imag;
public:
    Complex(double re = 0, double im = 0);
    Complex(const Complex& other);
    ~Complex();
    double getMagnitude() const;
    double getReal() const;
    double getImaginary() const;
    void print() const;
    void conjugate();
    void setReal(double r);
    void setImag(double r);
    Complex operator+(const Complex& y);
};
```


```
void bar(){  
    Complex x(1, 2);  
    Complex y(x);  
    Complex z(3, 4);  
    x = z;  
}
```

Assume execution has reached the last line of bar()
Which diagram correctly depicts the objects x, y, z
(and their values)


A



B



C












D: None of the above

```
void bar(){
    Complex x(1, 2);
    Complex y(x);
    Complex z(3, 4);
    x = z;
}
```

Pointers with the same value have the same color




Which pointers have the same value?



```
void bar(){
    Complex x(1, 2);
    Complex y(x);
    Complex z(3, 4);
    x = z;
}
```

Will calling bar() result in a seg fault?

- A. Yes
- B. No
- C. I don't know!



Assume:

- * **User-defined destructor**
- * **User-defined copy constructor**
- * **Default copy assignment**

RULE OF THREE

If a class defines one (or more) of the following it should probably explicitly define all three:

1. Destructor
2. Copy constructor
3. Copy assignment

We answered the following questions for the Complex class:

1. What is the behavior of these defaults?
2. What is the desired behavior ?
3. How should we over-ride these methods?

Questions to ask about any data structure:

- What operations does the data structure support?

A linked list supports the following operations:

1. push_front (add a value to the head)
 2. append/push_back (add a value to the tail)
 3. delete (a value)
 4. search (for a value)
 5. min
 6. max
 7. print all values
- How do you implement each operation?
 - How fast is each operation?

Linked List Abstract Data Type (ADT)

```
class LinkedList {  
public:  
    LinkedList();  
    ~LinkedList();  
    // other public methods  
  
private:  
    struct Node {  
        int info;  
        Node* next;  
    };  
    Node* head;  
    Node* tail;  
};
```

Memory Errors

- Memory Leak: Program does not free memory allocated on the heap.
- Segmentation Fault: Code tries to access an invalid memory location

```
void test_append_0(){
    LinkedList ll;
    ll.append(10);
    ll.print();
}
```

Assume:

- * **Default destructor**
- * **Default copy constructor**
- * **Default copy assignment**

What is the result of running the above code?

- A. Compiler error
- B. Memory leak
- C. Segmentation fault
- D. None of the above

Behavior of default copy constructor

```
void test_copy_constructor() {
    LinkedList l1;
    l1.append(1);
    l1.append(2);
    LinkedList l2(l1);
    // calls the copy c'tor
    l1.print();
    l2.print();
}
```

Assume:

destructor: user-defined

copy constructor: default

What is the output?

- A. Compiler error
- B. Memory leak
- C. Segmentation fault
- D. All of the above
- E. None of the above

Behavior of default copy assignment

I1 : 1 -> 2 -> 5 -> null

```
void default_assignment_1(LinkedList& l1){  
    LinkedList l2;  
    l2 = l1;  
}
```

- * What is the behavior of the default assignment operator?

Assume:

- * **User-defined destructor**
- * **Default copy constructor**
- * **Default copy assignment**

Behavior of default copy assignment

```
void test_default_assignment_2() {
    LinkedList l1, l2;
    l1.append(1);
    l1.append(2)
    l2 = l1;
    l2.print()
}
```

What is the result of running the above code?

- A. Prints 1 , 2
- B. Segmentation fault
- C. Memory leak
- D. A &B
- E. A, B and C

Assume:

- * **User-defined destructor**
- * **Default copy constructor**
- * **Default copy assignment**

Behavior of default copy assignment

```
void test_default_assignment_3(){
    LinkedList l1;
    l1.append(1);
    l1.append(2)
    LinkedList l2(l1);
    l2.append(10);
    l2.append(20);
    l2 = l1;
    l2.print()
}
```

What is the result of running the above code?

- A. Prints 1 , 2
- B. Segmentation fault
- C. Memory leak
- D. A &B
- E. A, B and C

Assume:

- * **User-defined destructor**
- * **User-defined copy constructor**
- * **Default copy assignment**

Overloading Operators

Overload relational operators for LinkedLists

`==`

`!=`

and possibly others

```
void test_equal(const LinkedList & lst1, const LinkedList & lst2){  
    if (lst1 == lst2)  
        cout<<"Lists are equal"<<endl;  
    else  
        cout<<"Lists are not equal"<<endl;  
}
```

Overloading Arithmetic Operators

Define your own addition operator for linked lists:

```
LinkedList 11, 12;
```

```
//append nodes to 11 and 12;
```

```
LinkedList 13 = 11 + 12 ;
```

Overloading input/output stream

Wouldn't it be convenient if we could do this:

```
LinkedList list;  
cout<<list; //prints all the elements of list
```

Next time

- Binary Search Trees